



Product Information		Lepro   LE	
Product conformity acc. to	:	Ecodesign requirements	
Supplier's name or trade mark	:	Lepro, LE	
Supplier's address	:	One Spencer Dock, North Wall Quay, Dublin 1, D01 X9R7, Ireland	
Model identifier	:	340015-DW-EU	
Model identifier of all equivalent models	:	340015-DW-EU	
With separate control gear	:	no	
<b>Type of light source</b>			
Lighting technology used	:	LED	Non-directional or directional
Mains or non-mains	:	NMLS	Connected light source(CLS)
Colour-tuneable light source	:	no	Envelope
High luminance light source	:	no	Anti-glare shield
Dimmable	:	no	
<b>General product parameters</b>			
Energy consumption in on-mode(kWh/1000h)	:	145.0	Energy efficiency class
Useful luminous flux, indicating if it refers to the flux in a sphere, in a wide cone or in a narrow cone (lm)	:	18000	Correlated colour temperature, rounded to the nearest 100K, or the range of correlated colour temperatures,rounded to the nearest 100K, that can be set
On-mode power(Pon),expressed in W	:	145.0	Standby power (Psb) expressed in W and rounded to the second decimal
Networked standby power(Pnet) for CLS, expressed in W and rounded to the second decimal	:	-	Colour rendering index, rounded to the nearest integer, or the range of CRI values that can be set
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts if any(mm)	Height	256	Spectral power distribution in the range 250nm to 800 nm at full-load
	Width	158	
	Depth	5	
Claim of equivalent power	:	-	If yes, equivalent power (W)
			Chromaticity coordinates (x and y)
<b>Parameters for directional light sources</b>			
Peak luminous intensity (cd)	:	-	Beam angle in degrees, or the range of beam angles that can be set
<b>Parameters for LED and OLED light sources</b>			
R9 colour rendering index value	:	10	Survival factor
the lumen maintenance factor	:	0.96	
<b>Parameters for LED and OLED mains light sources</b>			
displacement factor	:	0.9	Colour consistency in McAdam ellipses
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage	:	-	If yes then replacement claim (W)
Flicker metric (Pst LM)	:	-	Stroboscopic effect metric (SVM)




Declared/Measured values				
Voltage (V)	:	230AC		Useful luminous flux (lm) : 18000 in sphere
Frequency (Hz)	:	50		Luminance-HLLS (cd/mm <sup>2</sup> ) : - HLLS
On-mode power P <sub>on</sub> (W)	:	145		Beam angle (°) : - DLS
Standby power P <sub>sb</sub> (W)	:	0.05		Networked standby power P <sub>net</sub> (W) : - CLS
Displacement factor	:	0.95		CCT(K) : 6500
Colour consistency (SDCM)	:	5		CRI : 80
Flicker metric P <sub>stLM</sub>	:	-		Stroboscopic effect metric SVM : -
P <sub>onmax</sub> (W)	:	151.5		excitation purity for Blue 440nm-490nm : - CTLS
Total mains efficacy (lm/W)	:	124.1		excitation purity for Green 520nm-570nm : - CTLS
LB0750(H)	:	50000		excitation purity for Red 610nm-670nm : - CTLS
Parameters for separate control gear				
Voltage (V)	:	-		Maximum output power (W) : -
No-load power P <sub>no</sub> (W)	:	-		Efficiency in full load (%) : -
Standby power P <sub>sb</sub> (W)	:	-		Networked standby power P <sub>net</sub> (W) : -
the type of light sources for which it is intended	:	NMLS	LED	compatible dimmable light sources : only the together light source
Outer dimensions (mm)	Height	-		mass(g) : -
	Width	-		
	Depth	-		
$\eta_{TM} = (\Phi_{use}/P_{on}) \times FTM (lm/W)=124.1 lm/W$ <b>110 ≤ <math>\eta_{TM}</math> &lt; 135</b> energy efficiency class correspond to <b>E</b>				
Energy efficiency and functional requirements				
Classification acc. To 2019/2020		Directional lamp		<input checked="" type="checkbox"/> Non directional lamp
Compliance:	<input checked="" type="checkbox"/>	Yes		<input type="checkbox"/> No
Measurement conditions				
Standards	:	EU 2019/2015, EU 2019/2020		
Tolerances	:	according to ErP regulation		
Measurement setup	:	4P, SSL port, 1.5m sphere		
Voltage (V)	:	declared voltage		
Burning position	:	Base up		
Ambient temperature:	:	25°C +/- 2K		
Burn in	:	1h		
Total operating time during measurement	:	15min		
Non standard stability criteria	:	Luminous flux tolerance 0.5% within 60 sec.		
Uncertainties	:	according to JCGM (GUM) and CIE 198		
Important notes / WARNINGS:				
<b>1. This product contains replaceable light sources and separated control gears. The replaceable shall be the same model no. and brands.</b> <b>2. Separate the light source and control gears from the containing products at the end of life.</b> <b>3. The product needs to be powered off before install; Please see users' instruction</b>				
Signature	:	Vick Xun		

# Disassembly Instruction for removing LS and SCG


## Disassembly Instruction



1




2



3




6



5




4




7



8




9



12




1



10



13



14

Explanation text size : Arial 9 Black

Flow arrow used format

